



**MATERIALS:**

- HOSE: 321 Stainless Steel
- BRAID: 321 Stainless Steel
- NPT: Carbon Steel

| QTY. | PART No. | SIZE (in.) | OAL (in.) | W/P (psi) |        | WT. (lbs.) |
|------|----------|------------|-----------|-----------|--------|------------|
|      |          |            |           | 70°F.     | 250°F. |            |
|      | SECM-050 | 1/2        | 6-1/2     | 1250      | 1125   | .37        |
|      | SECM-075 | 3/4        | 7         | 725       | 650    | .50        |
|      | SECM-100 | 1          | 8         | 710       | 640    | .75        |
|      | SECM-125 | 1-1/4      | 8-1/2     | 550       | 495    | 1          |
|      | SECM-150 | 1-1/2      | 9         | 450       | 405    | 1.25       |
|      | SECM-200 | 2          | 10-1/2    | 350       | 315    | 2.12       |
|      | SECM-250 | 2-1/2      | 12        | 250       | 225    | 5          |
|      | SECM-300 | 3          | 14        | 300       | 270    | 8          |
|      | SECM-400 | 4          | 16        | 200       | 180    | 13         |

1. Units designed for pump vibration plus 1/8" misalignment.
2. For pulsating pressure, reduce working pressure by 50%.

CUSTOMER \_\_\_\_\_

PROJECT \_\_\_\_\_

ENGINEER \_\_\_\_\_

ARCHITECT \_\_\_\_\_

PRO./PO No. \_\_\_\_\_



**SOUTHEASTERN HOSE, INC.**  
Bremen, GA 30110

**BRAIDED CONNECTOR  
SUBMITTAL DATA**

DESCRIPTION: