



MATERIALS:

TUBE: Neoprene

COVER: Neoprene

REINFORCEMENT: Nylon

FEMALE UNIONS: Galvanized Steel

CONTROL UNITS: Steel Cable and Hardware

QTY.	PART No.	SIZE (in.)	OAL (in.)	W/P (psi) 125°F.	COMP. (in.)	ELONG. (in.)	LAT. (in.)	ANG. (°)	WT. (lbs.)
	SEMSDU-075	3/4	8	150	7/8	3/16	7/8	30	2
	SEMSDU-100	1	8	150	7/8	3/16	7/8	25	3
	SEMSDU-125	1-1/4	8	150	7/8	3/16	7/8	25	4
	SEMSDU-150	1-1/2	8	150	7/8	3/16	7/8	20	5
	SEMSDU-200	2	8	150	7/8	3/16	7/8	15	6
	SEMSDU-250	2-1/2	9	150	7/8	3/16	7/8	12	9
	SEMSDU-300	3	9	150	7/8	3/16	7/8	10	12

1. This flexible joint should be installed the length shown on drawing.
2. Piping and equipment connected by this flexible joint must be properly anchored and/or guided.
3. Not intended for torsion.

CUSTOMER _____
 PROJECT _____
 ENGINEER _____
 ARCHITECT _____
 PRO./PO No. _____



SOUTHEASTERN HOSE, INC.
 Bremen, GA 30110

DOUBLE SPHERE FEMALE UNION
 w/ CONTROL UNITS
SUBMITTAL DATA

DESCRIPTION: