



**MATERIALS:**

TUBE: Neoprene

COVER: Neoprene

REINFORCEMENT: Nylon Tire Cord

FLANGE: Zinc Plated Steel

QTY.	PART No.	SIZE (in.)	OAL (in.)	WIP (psi) 230°F.	COMP. (in.)	ELONG. (in.)	LAT. (in.)	ANG. (°)	VAC. (in. Hg.)	WT. (lbs.)
	SEMS-150	1-1/2	6	220	1/2	3/8	1/2	15	16	8
	SEMS-200	2	6	220	1/2	3/8	1/2	15	16	9
	SEMS-250	2-1/2	6	220	1/2	3/8	1/2	15	16	12
	SEMS-300	3	6	220	1/2	3/8	1/2	15	16	15
	SEMS-400	4	6	220	5/8	3/8	1/2	15	16	18
	SEMS-500	5	6	220	5/8	3/8	1/2	15	16	25
	SEMS-600	6	6	220	5/8	3/8	1/2	15	16	28
	SEMS-800	8	6	220	5/8	3/8	1/2	15	16	40
	SEMS-1000	10	8	220	3/4	1/2	3/4	15	16	58
	SEMS-1200	12	8	220	3/4	1/2	3/4	15	16	75
	SEMS-1400	14	8	114	3/4	1/2	3/4	15	16	95
	SEMS-1600	16	8	114	3/4	1/2	3/4	15	16	110
	SEMS-1800	18	8	114	3/4	1/2	3/4	15	16	130
	SEMS-2000	20	8	114	3/4	1/2	3/4	15	16	148

CUSTOMER \_\_\_\_\_  
 PROJECT \_\_\_\_\_  
 ENGINEER \_\_\_\_\_  
 ARCHITECT \_\_\_\_\_  
 PRO./PO No. \_\_\_\_\_



**SOUTHEASTERN HOSE, INC.**  
 Bremen, GA 30110

**SINGLE SPHERE RUBBER CONNECTOR  
 SUBMITTAL DATA**

DESCRIPTION: